



TG 10 Series ▶

Technical Specifications

Voltage : 380 V | Pole : 20 | Duty Cycle : S5 40% | Brake Voltage : 110 V DC | Max. Static Load : 3000 kg

Model No.	Duty Load(kg)	Passnager Capacity	Speed (m/s)	Sheave Dia (mm)	Roping	No. of Ropes	Rope Dia (mm)	Rated current (A)	Power (KW)	RPM	Torque (Nm)	Rated Frequency (Hz)	IP Protection	Start / Hr.	Machine Weight (kg) Approx
TG 1010 A-340	680	10	0.50	340	2:1	5	8	7.0	2.3	56	395	9.40	IP 41	180	350
TG 1010 C-340	680	10	1.00	340	2:1	5	8	12.3	4.6	112	395	18.70	IP 41	180	350
TG 1010 E-340	680	10	1.50	340	2:1	5	8	17.6	6.9	168	395	28.00	IP 41	180	350
TG 1012 A-340	816	12	0.50	340	2:1	5	8	7.3	2.8	56	525	9.40	IP 41	180	350
TG 1012 C-340	816	12	1.00	340	2:1	5	8	16.5	6.4	112	525	18.70	IP 41	180	350
TG 1014 A-400	952	14	0.50	400	2:1	5	10	8.0	2.7	48	590	8.00	IP 41	180	350
TG 1014 C-400	952	14	1.00	400	2:1	5	10	13.5	5.9	96	590	16.00	IP 41	180	350
TG 1016 A-400	1088	16	0.50	400	2:1	5	10	9.0	3.4	48	670	8.00	IP 41	180	350
TG 1016 C-400	1088	16	1.00	400	2:1	5	10	15.7	6.7	96	670	16.00	IP 41	180	350

